



**MOKAY**<sup>®</sup>  
— COATING EXPERT —

# MOKAY DIAMOND PRIMER



MOKAY<sup>®</sup> Diamond Primer is formulated with advanced emulsion resin and selected imported materials. Designed to improve cement substrate performance, it effectively reduces water absorption and enhances waterproofing efficiency. When used in combination with MOKAY<sup>®</sup> Diamond Master, it delivers enhanced waterproof protection and long-term durability. The primer also provides excellent bonding strength across a wide range of substrates, including ceramic, glass, PVC, metal, and aluminum.

## APPLICATION METHODS

Apply directly using a roller.

## PREPARATION

Ensure the wall or floor is dry, solid, clean and free from any dust or grease residue. For PU or waterproof-coated surfaces, mechanically abrade the surface, clean thoroughly, and allow it to dry completely before application.

## APPLICATION PROCEDURES

Apply one coat of MOKAY<sup>®</sup> Diamond Master Primer evenly with roller or spray gun and allow it to dry completely.

## CLEAN UP

Clean tools and equipment with soap and water. Properly dispose of used rags and protect unused product from freezing.

## MATCHED PRODUCTS

The use of Mokay matched primer, middle coat, and topcoat as a complete system is recommended for optimal finish performance.



## FEATURES



Easy  
Application



Low Voc  
And Odorless



Eco  
Friendly



Strong  
Penetration



High  
Adhesion



Multi-Substrate  
Compatibility

## NOTICE

- Stir thoroughly after opening the paint can. To prevent hardening, keep the can tightly closed during application intervals. Do not return thinned paint to the original container.
- Do not apply when the temperature is below 10°C or when relative humidity exceeds 85%.
- For information on Manufacturing Date, Lot Number, Net Content, and Expiry Date, please refer to the product label.

Store in a cool, dry, and well-ventilated place. Shelf life is 18 months when stored in the original unopened container at temperatures between 0°C and 35°C.

## PACKING

0.5KG

1KG

5KG

18KG

\* 18KG Coverage: 400-450m<sup>2</sup>/layer


## APPLICATION AREAS


INTERIOR WALLS

EXTERIOR WALLS

FLOORS

Ceramic Tiles / Marble / Pvc / Glass / Metal / Calcium Silicate Board / Partition Board / Plywood / Leather


 Never pour paint down the drain or bury it. Avoid runoff into storm sewers, ditches and waterways.

 To recycle or properly dispose of paint, consult with your local waste requirements or guidelines, if applicable, to ensure compliance.



**mokaymalaysia.com**

    mokaymalaysia

 +604-611 7363 / +604-645 2873

 info@mokaymalaysia.com



**Penang (Headquarter)**  
4L, Tingkat Kenari, Sungai Ara,  
11900 Bayan Lepas,  
Penang, Malaysia.

**Selangor (Branch)**  
41, Jalan Utara PJS 12,  
Petaling Jaya, 46200  
Selangor, Malaysia.