



MOKAY[®]
— COATING EXPERT —

DIAMOND MASTER FLOOR

A fully exposable waterproof system built to withstand extreme weather and daily foot traffic.

MOKAY[®] DIAMOND MASTER FLOOR is an innovative waterproof coating developed to address common wall issues such as water permeability, mold growth, surface darkening, blistering, and peeling. It is formulated with imported high-performance modified polyurethane resin and specialty additives, reinforced with alkali-resistant, crack-resistant glass fibers to enhance waterproofing performance without the need for polyester fabric reinforcement.

Featuring high strength, excellent water resistance, crack resistance, tensile strength, weather durability, and UV resistance, it is suitable for exterior wall refurbishment, waterproofing, and decorative applications. With strong adhesion, it can be applied to a wide range of substrates including cement, putty, ceramic tiles, metal, wood, glass, and plastics.

PRODUCT FEATURES



Waterproof and Weather Resistant
UV protection, Waterproof.



Anti-Fungus
Protection against fungus and mold.



Environmentally Friendly
Low VOC & odor. Energy savings.



Hassle-Free Maintenance
Clean with damp cloth or brush.



Designed to withstand regular
foot traffic.



Hassle-Free Application
Easy application with roller or brush.



Anti-Cracking properties
Exceptional durability and flexibility.



Excellent adhesion to substrates,
ensuring long-lasting performance.

APPLICATION TECHNIQUE

PREPARATION:

Apply a suitable primer evenly onto the prepared substrate and allow to dry for 3–4 hours. Apply 1–2 coats as required; for powdery or sandy surfaces, apply 2–3 coats. Proceed only after the primer has fully cured.

PACKAGING:

Weight : 20 KG
Coverage : 40-45m²/3layers

STEP 1 | FIRST COAT APPLICATION

Apply the first coat of Mokay Diamond Floor evenly. Allow to dry for approximately 6–8 hours.

STEP 2 | SECOND COAT APPLICATION


Apply the second coat of Mokay Diamond Floor evenly. Allow to dry for approximately 6–8 hours.

*** Full curing is achieved after approximately 7 days.**

IMPORTANT:

Color variations may occur based on application technique and the quantity of material used.

APPLICATION RESULTS



Before



After



mokaymalaysia.com

    [mokaymalaysia](https://www.mokaymalaysia.com)

 +604-611 7363 / +604-645 2873

 info@mokaymalaysia.com



Penang (Headquarter)
4L, Tingkat Kenari, Sungai Ara,
11900 Bayan Lepas,
Penang, Malaysia.

Selangor (Branch)
41, Jalan Utara PJS 12,
Petaling Jaya, 46200
Selangor, Malaysia.