



**MOKAY**<sup>®</sup>  
— COATING EXPERT —

# Waterproofing Series **Diamond Master INTERMEDIATE**

**DIAMOND MASTER INTERMEDIATE** is premium fiber reinforced waterproof coating. It's crafted with precision, our formula combines Ethylene-Vinyl Acetate, special acrylic, alkali-resistant glass fiber, and silicon crystal aggregate powder. This unique blend creates a supremely elastic and durable waterproofing system. With superior adhesion and weather resistance, trust **DIAMOND MASTER INTERMEDIATE** to protect and endure in any environment.

## PRODUCT FEATURES



**Excellent waterproofing.**  
Fiber reinforced waterproof coating.



**Anti-crack and high elasticity.**  
Excellent tensile strength and superior substrate adhesion.



**Alkali resistant glass fiber.**  
Improve structural. Resistant to minor earthquake.



**Environmentally Friendly.**  
Low VOC and odorless. Energy savings.



**Hassle-Free Application.**  
Easy application with roller or brush.

## SCOPE OF APPLICATION:

Ideal for intermediate waterproofing systems, both internal and external walls, rooftops, balconies, courtyards, bathrooms, swimming pools, ponds and any other construction requiring waterproofing.

## PRODUCT DESCRIPTION

### APPLICATION INTERVAL :

At least 4 hours to 6 hours

(Depending on site and weather conditions)

**Tools :** Roll, brush, construction spatula

**Packaging weight :** 5 KG

**Product viscosity :** 33.000-38.000 mpas @25°C

### Best before :

At least 24 months under normal circumstances

**Standard color :** 828 (Grey)

**Coverage :** 4.5-4.7m<sup>2</sup>/2layers

### Products storage method :

Please keep in a cool and ventilated place.

Do not expose to sun. Store within 10-35°C

## APPLICATION METHOD

### SURFACE PREPARATION:

- Ensure substrate is clean and free of dust, dirt, oil, grease, paint, curing compound, concrete sealers, loosely bonded toppings and any other substances that may prevent or reduce adhesion. If the substrate contains these substances, they must be removed. All cracks and hollow spots must be addressed and repaired.
- During application, water drainage outlets must be sealed to avoid blockage.
- Apply 1 layer of primer and let it dry, then apply 2 layers of base coat.


### WATERPROOFING APPLICATION:


- Recommended not to dilute the product for maximum performance.
- Open cover and stir well using metal stir bar. (Do not use electric stir bar for stirring) Please use cross line method to apply first and second layer. This product is recommended to apply 2-3 layers to achieve maximum performance.
- Able to apply or install on any tiles, cement mortar products and paint on top of waterproofing material after it is fully cured.





**mokaymalaysia.com**

    **mokaymalaysia**

 +604-611 7363 / +604-645 2873

 **info@mokaymalaysia.com**

 **Penang (Headquarter)**  
4L, Tingkat Kenari, Sungai Ara,  
11900 Bayan Lepas,  
Penang, Malaysia.

 **Selangor (Branch)**  
41, Jalan Utara PJS 12,  
Petaling Jaya, 46200,  
Selangor, Malaysia.

