



# MOKAY NANO PRIMER



**Mokay® Nano Primer** is formulated with a water-based pure acrylic emulsion, offering excellent penetration into the substrate. It penetrates to an effective depth to consolidate weak or porous surfaces and uniformly reduce water absorbency.

By enhancing surface integrity, **Mokay® Nano Primer** improves adhesion between the substrate and subsequent topcoats. It also helps to block moisture and chemical intrusion, creating a stable base that enhances application performance and overall finish quality.

## FEATURES



Surface  
Sealing



Improves Finish  
Painting Quality



Strong  
Penetration



Multi-Substrate  
Compatibility



High  
Adhesion

## APPLICATION METHODS

Apply Mokay® Nano Primer directly onto the substrate using a brush or spray gun.

## PREPARATION

Ensure the wall or floor is dry, solid, clean and from any dust or grease residue. Repair any hollows, cracks, or loose areas prior to application.

## APPLICATION PROCEDURES

Apply Mokay® Nano Primer directly onto the substrate using a brush or spray gun.

## CLEAN UP

Clean tools and equipment with soap and water. Properly dispose of used rags and protect unused product from freezing.

## MATCHED PRODUCTS

The use of Mokay matched primer, middle coat, and topcoat as a complete system is recommended for optimal finish performance.





## NOTICE

- Stir thoroughly after opening the paint can. To prevent hardening, keep the can tightly closed during application intervals. Do not return thinned paint to the original container.
- Do not apply when the temperature is below 10°C or when relative humidity exceeds 85%.
- For information on Manufacturing Date, Lot Number, Net Content, and Expiry Date, please refer to the product label.

Store in a cool, dry, and well-ventilated place. Shelf life is 18 months when stored in the original unopened container at temperatures between 0°C and 35°C.

## PACKING

0.5KG

1KG

5KG

18KG

## APPLICATION AREAS

INTERIOR WALLS

EXTERIOR WALLS

Cement / Mortar / Masonry Wall / High-Alkali Substrate / Water-Absorbing or Loose Surfaces



Never pour paint down the drain or bury it. Avoid runoff into storm sewers, ditches and waterways.



To recycle or properly dispose of paint, consult with your local waste requirements or guidelines, if applicable, to ensure compliance.



**mokaymalaysia.com**



mokaymalaysia



+604-611 7363 / +604-645 2873



info@mokaymalaysia.com



4L, Tingkat Kenari, Sungai Ara,  
11900, Bayan Lepas, Penang,  
Malaysia.

\* The product images in this catalog may vary slightly due to differences in lighting conditions and printing processes.  
\* We recommend examining actual product samples before making an order.