



**MOKAY**<sup>®</sup>  
— COATING EXPERT —

# MOKAY TOPCOAT MATT | GLOSS



**Mokay® Topcoat Matt | Gloss** is formulated with a water-based silicone resin system. It offers excellent resistance to stains, alkali, dust, and weathering, providing long-lasting surface protection and a durable matte finish.

## APPLICATION PROCEDURES

Apply one or two coats evenly over the prepared coating surface as required.

## CLEAN UP

Clean tools and equipment with soap and water. Properly dispose of used rags and protect unused product from freezing.

## MATCHED PRODUCTS

The use of Mokay matched primer, middle coat, and topcoat as a complete system is recommended for optimal finish performance.

## FEATURES



Easy  
Application



Alkali  
Resistance



Weather  
Resistance



Water & Fungus  
Resistance



High  
Adhesion



Color  
Retention

## NOTICE

- Stir thoroughly after opening the paint can. To prevent hardening, keep the can tightly closed during application intervals. Do not return thinned paint to the original container.
- Do not apply when the temperature is below 10°C or when relative humidity exceeds 85%.
- For information on Manufacturing Date, Lot Number, Net Content, and Expiry Date, please refer to the product label.

Store in a cool, dry, and well-ventilated place. Shelf life is 18 months when stored in the original unopened container at temperatures between 0°C and 35°C.

## PACKING

0.5KG

1KG

5KG

18KG

## APPLICATION AREAS

INTERIOR WALLS

EXTERIOR WALLS

Stone Paint / Texture Paint / Granite Paint / Decorative Coatings



Never pour paint down the drain or bury it. Avoid runoff into storm sewers, ditches and waterways.



To recycle or properly dispose of paint, consult with your local waste requirements or guidelines, if applicable, to ensure compliance.



**mokaymalaysia.com**



+604-611 7363 / +604-645 2873



info@mokaymalaysia.com



4L, Tingkat Kenari, Sungai Ara,  
11900, Bayan Lepas, Penang,  
Malaysia.

\* The product images in this catalog may vary slightly due to differences in lighting conditions and printing processes.  
\* We recommend examining actual product samples before making an order.